



Wall mounted Seasonal Classic

FAQ-C9 / RZQSG-L Seasonal Classic

A discreet option for many applications



Wall mounted units are able to be fixed to almost any wall, leaving space for furniture, decoration and fittings. Wall mounted units have modern looks, and reduced size and weight, making them a discreet option for many applications.

Comfort levels in a room can be improved due to new airflow and air discharge settings, accessed via the wired remote controller. The controller can also be set to restrict room occupants from changing settings, preventing over-heating or cooling.

Wall mounted units and Seasonal Classic condensers can be used as cost effective replacements for old equipment as they are able to use existing R22 and R407C pipe-work.

The air is comfortably spread up- and downwards thanks to 5 different discharge angles that can be programmed via the remote control.

Maintenance operations can be performed easily from the front of the unit.



RZQSG100L8V1



BRC1E53A



BRC7CB58
(optional)



FAQ-C9

FAQ-C9 / RZQSG-L

Features	Benefits
Automatic airflow volumes control	Adjusts fan speed to match difference between room and set temperature, unit works smarter without need for occupants to change settings
Vertical and horizontal auto-swing	Allows better air and temperature distribution, giving a room more uniform conditions
D3 connection as standard	Allows integration of split system into Daikin building management systems
R22 Replacement technology	Re-use of existing R22 and R407C piping possible, allowing only fan-coil and condensers to be replaced
Install flexibility	Piping can be installed in one of 6 positions on the unit, giving greater flexibility of siting the unit on a wall

Indoor Units			Single Phase		3 Phase
			FAQ71C9	FAQ100C9	FAQ100C9
Capacity	UK Total Cooling	kW	7.28	10.80	10.80
	UK Sensible Cooling	kW	4.99	7.44	7.44
	Nominal Cooling	kW	6.80	9.50	9.50
	Nominal Heating	kW	7.50	10.80	10.80
Seasonal Efficiency (EN14825) COOLING	Energy Label		A+	A+	A+
	Pdesign	kW	6.80	9.50	9.50
	SEER		5.18	5.61	5.61
	Annual Energy Consumption	kWh	410	593	593
Seasonal Efficiency (EN14825) HEATING	Energy Label		A	A+	A+
	Pdesign	kW	6.13	6.81	6.81
	SCOP		3.90	4.01	4.01
	Annual Energy Consumption	kWh	2273	2378	2378
Nominal Efficiency	EER / COP		3.21 / 3.61	3.01 / 3.41	3.01 / 3.41
	Energy Label		A / A	B / B	B / B
	Annual Energy Consumption	kWh	1060	1580	1580
Air Flow Rate (Cooling)	High / Nom / Low	m ³ /sec	0.300 / 0.267 / 0.233	0.433 / 0.383 / 0.317	0.433 / 0.383 / 0.317
Dimensions	Height	mm	290	340	340
	Width	mm	1050	1200	1200
	Depth	mm	238	240	240
Weight		kg	13	17	17
Sound Pressure (Cooling)	High / Nom / Low	dBA	45 / 42 / 40	49 / 45 / 41	49 / 45 / 41
Sound Power (Cooling)		dBA	61	65	65

Outdoor Units			RZQSG71L3V1	RZQSG100L9V1	RZQSG100L8Y1
Dimensions	Height x Width x Depth	mm	770 x 900 x 320	990 x 940 x 320	990 x 940 x 320
Weight		kg	67	72	82
Electrical Details	Power Supply		1ph		3ph
	Running Current	A	8.66	12.91	4.86
	Starting Current	A	4	4	4
	Max Fuse Size	A	20	32	20
Interconnection Wiring	Core / Cable size		3+E / 1.5		3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	3/8 (9.5) / 5/8 (15.9)		3/8 (9.5) / 5/8 (15.9)
Pipework	Maximum Length	m	50	50	50
	Maximum Vertical Rise	m	15	30	30
	Precharged to	m	30	30	30
	Additional Charge	g/m	Refer to Installation Manual		Refer to Installation Manual
	Holding Charge	kg	2.75	2.9	2.9
Sound Pressure (Cooling)	Nom / Night Quiet	dBA	49 / 47	53 / 49	53 / 49
Sound Power (Cooling)		dBA	65	70	70
Air Flow Rate (Cooling)	Nominal	m ³ /sec	0.866	1.266	1.266

Accessories

Wireless remote controller (BRC7EB518)

Drain plug kit (K-KDU572EVE)

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com