




FCAG-A / RXM-M9

R-32 BLUEEVOLUTION

360° air discharge for optimum efficiency and comfort

- › Combination with split outdoor units is ideal for small retail, offices or residential applications
- › Lowest installation height in the market: 204mm for class 71
- › Individual louvre control: flexibility to suit every room layout without changing the location of the unit
- › Modern style decoration panel is available in 3 different variations: white (RAL9010) with grey louvers, full white (RAL9010) or Auto-cleaning panel
- › Automatic filter cleaning results in higher efficiency & comfort and lower maintenance costs. 2 filters available: standard filter and finer mesh filter (for fine dust applications i.e. clothing shops)
- › Two optional intelligent sensors improve energy efficiency and comfort
- › No optional adapter needed for DIII-connection, link your unit directly into the wider building management system
- › Branch duct discharge allows to optimize air distribution in irregular shaped rooms or to supply air to small adjacent rooms
- › Reduced energy consumption thanks to specially developed small tube exchanger, DC fan motor and drain pump
- › Optional fresh air intake
- › Standard drain pump with 675mm lift increases flexibility and installation speed



FCAG-A



RXM42-60M9



BRC1E53A



BRC7FA532F
(optional)



BRP069A81
(optional)



WI-FI ADAPTOR
AVAILABLE AS AN OPTION

FCAG-A / RXM-M9

R-32 BLUEEVOLUTION

Indoor Units			FCAG35A	FCAG50A	FCAG60A
Capacity	UK Total Cooling	kW	3.32	4.89	5.57
	UK Sensible Cooling	kW	2.29	3.26	3.67
	Nominal Cooling	kW	3.5	5.0	5.7
	Nominal Heating	kW	4.2	6.0	7.0
Seasonal Efficiency (EN14825) COOLING	Energy Label		A++	A++	A++
	Pdesign	kW	3.5	5.0	5.7
	SEER		6.35	6.54	6.40
	Annual Energy Consumption	kWh	193	266	312
Seasonal Efficiency (EN14825) HEATING	Energy Label		A++	A+	A+
	Pdesign	kW	3.32	4.36	4.71
	SCOP		4.9	4.3	4.2
	Annual Energy Consumption	kWh	948	1419	1569
Nominal Efficiency	EER/COP		3.72/3.77	3.58/3.70	3.31/3.38
Air Flow Rate (Cooling)	High / Nom / Low	m ³ /sec	0.208/0.176/0.145	0.210/0.178/0.145	0.226/0.186/0.145
Dimensions (with Decoration Panel)	Height	mm	204 (264)	204 (264)	204 (264)
	Width	mm	840 (950)	840 (950)	840 (950)
	Depth	mm	840 (950)	840 (950)	840 (950)
Weight (with Decoration Panel)		kg	18 (23.4)	19 (24.4)	19 (24.4)
Sound Pressure (Cooling)	High / Nom / Low	dBA	31/29/27	31/29/27	33/31/28
Sound Pressure (Heating)	High / Nom / Low	dBA	31/29/27	31/29/27	33/31/28
Sound Power (Cooling)		dBA	49	49	51

Outdoor Units			RXM35M9	RXM50M9	RXM60M9
Dimensions	Height x Width x Depth	mm	550 x 765 x 285	735 x 825 x 300	735 x 825 x 300
Weight		kg	32	47	47
Electrical Details	Power Supply		1ph	1ph	1ph
	Running Current	A	-	-	-
	Starting Current	A	-	-	-
	Max Fuse Size	A	10	15	15
Interconnection Wiring	Core / Cable Size		3+E / 1.5	3+E / 1.5	3+E / 1.5
Piping Connections	Liquid / Gas	inches (mm)	1/4 (6.4) / 3/8 (9.5)	1/4 (6.4) / 1/2 (12.7)	1/4 (6.4) / 1/2 (12.7)
Pipework	Maximum Length	m	20	30	30
	Maximum Vertical Rise	m	20	20	20
	Precharged to	m	10	10	10
	Additional charge	g/m	20	20	20
	Holding charge	kg	0.76	1.40	1.45
Sound Pressure (Cooling)	Nominal	dBA	49	48	48
Sound Pressure (Heating)	Nominal	dBA	49	49	49
Sound Power (Cooling)		dBA	61	62	63
Operating Range (Cooling)	Min / Max	°CDB	-10/46	-10/46	-10/46
Operating Range (Heating)	Min / Max	°CWB	-15/18	-15/18	-15/18
Air Flow Rate (Cooling)	Nominal	m ³ /sec	0.600	0.840	0.840
ECA Eligible			●	●	●

Accessory Ref	Description
BRC1E53A	Premium wired remote controller (Included as standard)
BYCQ140D	Decoration panel (Included as standard)
BRP069A81	Wifi adaptor for connection to on-line controller
BRC7FA532F	Wireless remote controller
BRYQ140A	Integral PIR sensor for roundflow decoration panel. Enables energy saving functions
BYCQ140DG9	Roundflow cassette decoration panel with self cleaning filter
BYCQ140DGF9	New Roundflow cassette decoration panel with fine self cleaning filter
BYCQ140DW	Roundflow cassette decoration panel - white with white louvres
K.CGM	Condensing unit guard size 42-71
K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
K.DT1	Condensate drip tray for use with K.CWB90-2
K.RSS	Wireless room mounted temperature sensor and receiver

Accessory Ref	Description
KDBHQ55B140	Sealing member for air discharge outlet
KDDP55C160-1	Fresh air intake kit for up to 20% fresh air (Part 1)
KDDQ55B140-2	Fresh air intake kit for up to 20% fresh air (Part 2)
KLIC-DI	KNX Interface for Sky Air and VRV systems
KRCS01-4	Remote room mounted temperature sensor
KRP4A53 and UK.FB2	Unit/group adaptor PCB for remote on/off, status indication and temperature setting
RS-SE	Service and configuration tool for K.RSS
RTD-10 and UK.FB2	Enhanced function PCB for Sky Air and VRV. Duty rotation, Lead Lag control and heating interlock
RTD-20 and UK.FB2	Energy control PCB for Sky Air and VRV
RTD-NET and UK.FB2	Modbus interface PCB for Sky Air and VRV

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com